

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	<b>TM DESANA MAX FP</b>
Registration number (REACH)	not relevant (mixture)
<b>Unique formula identifier (UFI)</b>	<b>3910-Y0CA-S00C-RQJK</b>

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	cleaning agent biocidal product Sanitizer (Others) professional use (SU2) industrial use (SU3)
Uses advised against	do not use for squirting or spraying do not use for products which come into direct contact with the skin

#### 1.3 Details of the supplier of the safety data sheet

Thonhauser GmbH  
Perlhofgasse 2/1  
2372 Giesshübl/Wien  
Austria

Telephone: +43 (0)2236 320 272  
Telefax: +43 (0)2236 320 273  
e-mail: QA@thonhauser.net  
Website: www.afcocare.eu

#### **Additional information**

Manufacturer					
Country	Name	Postal code/city	Telephone	Telefax	website
Austria	Thonhauser GmbH	2372 Giesshübl	+43 2236 320 272	+43 2236 320 273	www.afcocare.eu
United Kingdom	AFCO C&S Ltd	UK, M26 2GL Manchester	+44 161 796 6333		www.afcocare.com

e-mail (competent person) QA@thonhauser.net (Herr Dr. Daniel Herzog)

#### 1.4 Emergency telephone number

Manufacturer **+43 699 141 80 200**  
Mon - Thu 07:00 - 15:00, Fri 07:00 - 13:00

#### Poison centre & Emergency information service

United Kingdom	CHEMTREC UK 24/7 CCN 819393	+44 870 8200418
----------------	--------------------------------	-----------------

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
**TM DESANA MAX FP**

Version number: GHS 16.0  
 Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	1A	Skin Corr. 1A	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.4R	Respiratory sensitisation	1	Resp. Sens. 1	H334
3.4S	Skin sensitisation	1	Skin Sens. 1	H317

For full text of H-phrases: see SECTION 16.

#### The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word **danger**

- Pictograms

GHS05, GHS08



- Hazard statements

H290 May be corrosive to metals.  
 H314 Causes severe skin burns and eye damage.  
 H317 May cause an allergic skin reaction.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

- Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling sodium hydroxide, disodium peroxodisulphate

### 2.3 Other hazards

There is no additional information.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
**TM DESANA MAX FP**

Version number: GHS 16.0  
 Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28










## SECTION 3: Composition/information on ingredients

### 3.1 Substances

not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Conc.	Classification acc. to GHS	Pictograms	M-Factors
Sodium hydroxide	CAS No 1310-73-2  EC No 215-185-5	50 – < 75 wt%	Met. Corr. 1 / H290 Skin Corr. 1A / H314 Eye Dam. 1 / H318		
Potassium nitrate	CAS No 7757-79-1  EC No 231-818-8	5 – < 10 wt%	Ox. Sol. 3 / H272		
Disodium peroxodisulphate	CAS No 7775-27-1  EC No 231-892-1	5 – < 10 wt%	Ox. Sol. 3 / H272 Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 STOT SE 3 / H335	  	
Sodium permanganate	CAS No 10101-50-5  EC No 233-251-1	< 1 wt%	Ox. Sol. 2 / H272 Acute Tox. 4 / H302 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	   	M-Factor (acute) = 10.0

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
Sodium hydroxide	Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Dam. 1; H318: C ≥ 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	-	-	
Disodium peroxodisulphate	-	-	1,200 mg/kg	Oral
Sodium permanganate	-	M-Factor (acute) = 10.0	500 mg/kg	Oral

For full text of abbreviations: see SECTION 16.

### Regulation 528/2012/EU concerning the making available on the market and use of biocidal products

Biocidal active substances		
Name of substance	% (w/w)	unit
Disodium peroxodisulphate	64	g/kg

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures



##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Rinse skin with water/shower.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Ideally, use the PREVIN® solution as the first rinse. Use all of the content. If the PREVIN® solution is not immediately available, rinse with water first and then as soon as possible with the PREVIN® solution.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

water, foam, alcohol resistant foam, ABC-powder

##### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

##### Hazardous combustion products

nitrogen oxides (NO<sub>x</sub>), phosphorus oxides (P<sub>x</sub>O<sub>y</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### **For non-emergency personnel**

Remove persons to safety.

##### **For emergency responders**

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

##### **Advice on how to contain a spill**

covering of drains, take up mechanically

##### **Advice on how to clean up a spill**

Take up mechanically. Absorbents and binders, neutralising agents.

##### **Appropriate containment techniques**

Neutralisation techniques.

##### **Other information relating to spills and releases**

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Incompatible substances or mixtures: see section 7. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### **Recommendations**

##### **- Measures to prevent fire as well as aerosol and dust generation**

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.

##### **- Specific notes/details**

Dust deposits may accumulate on all deposition surfaces in a technical room.

##### **- Handling of incompatible substances or mixtures**

Do not mix with acids.

##### **- Keep away from**

acids

##### **- Advice on general occupational hygiene**

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### **Managing of associated risks**

##### **- Explosive atmospheres**

Removal of dust deposits.

##### **- Corrosive conditions**

Store in corrosive resistant container with a resistant inner liner.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### - Incompatible substances or mixtures

Prohibition of joint storage (with): acids

### - Floors

The materials shall display sufficient resistance to the prevalent chemical conditions (Caustic solutions).

### - Protect against external exposure, such as

frost

### - Consideration of other advice

Observe technical data sheet.

Lagerklasse (storage class according to TRGS 510, Germany): 8 B (non-combustible corrosive materials (except only corrosive to metals))

### - Ventilation requirements

Use local and general ventilation.

### - Specific designs for storage rooms or vessels

Floors: The materials shall display sufficient resistance to the prevalent chemical conditions (Caustic solutions).

### - Packaging compatibilities (Receptacles / Material)

Only packagings which are approved (e.g. acc. to ADR) may be used.

## 7.3 Specific end use(s)

These information are not available.

## 7.4 Other information

storage temperature of 0 °C and up to 20 °C  
recommended storage temperature: 5 - 20 °C

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
GB	Dust		WEL		10					i	EH40/2005
GB	Dust		WEL		4					r	EH40/2005
GB	Sodium hydroxide	1310-73-2	WEL				2				EH40/2005

#### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur.

i Inhalable fraction.

r Respirable fraction.

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified).

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified).

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sodium hydroxide	1310-73-2	DNEL	1 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - local effects
Potassium nitrate	7757-79-1	DNEL	20.8 mg/kg	Human, dermal	Worker (industry)	Chronic - systemic effects
Potassium nitrate	7757-79-1	DNEL	36.7 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Disodium peroxodisulphate	7775-27-1	DNEL	2.06 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - local effects
Disodium peroxodisulphate	7775-27-1	DNEL	18.2 mg/kg	Human, dermal	Worker (industry)	Chronic - systemic effects
Disodium peroxodisulphate	7775-27-1	DNEL	2.06 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Sodium permanganate	10101-50-5	DNEL	0.05 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Sodium permanganate	10101-50-5	DNEL	0.05 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Acute - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Potassium nitrate	7757-79-1	PNEC	0.45 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
Potassium nitrate	7757-79-1	PNEC	0.045 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
Potassium nitrate	7757-79-1	PNEC	18 mg/l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)
Potassium nitrate	7757-79-1	PNEC	4.5 mg/l	Aquatic organisms	Water	Intermittent release
Disodium peroxodisulphate	7775-27-1	PNEC	0.0763 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
Disodium peroxodisulphate	7775-27-1	PNEC	3.6 mg/l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)
Disodium peroxodisulphate	7775-27-1	PNEC	0.275 mg/kg	Benthic organisms	Sediments	Short-term (single instance)
Disodium peroxodisulphate	7775-27-1	PNEC	0.0396 mg/kg	Pelagic organisms	Sediments	Short-term (single instance)
Disodium peroxodisulphate	7775-27-1	PNEC	0.015 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
Disodium peroxodisulphate	7775-27-1	PNEC	0.763 mg/l	Aquatic organisms	Water	Intermittent release
Disodium peroxodisulphate	7775-27-1	PNEC	0.011 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
Sodium permanganate	10101-50-5	PNEC	0 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Sodium permanganate	10101-50-5	PNEC	0 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
Sodium permanganate	10101-50-5	PNEC	1.64 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)



#### Eye/face protection

Wear eye/face protection. Use safety goggles with side protection. Use protective eyewear to guard against splash of liquids. EN 166.

#### Skin protection

##### - Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### - Protective gloves - Splash protection

Recommended protective gloves (trademark/manufacturer): UVEX u-chem UVEX u-fit,

##### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Chemical protective clothing

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Combination filtering device (EN 141). Particulate filter device (EN 143).

#### Environmental exposure controls

Before discharge of the waste water into a municipal waste water treatment facility the product normally needs to be neutralised.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	solid
Colour	violet
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	non-combustible
Lower and upper explosion limit	not determined
Flash point	not applicable
Auto-ignition temperature	not determined
Decomposition temperature	not relevant
pH (value)	12.2 – 13 (in aqueous solution: 10 <sup>g/l</sup> , 20 °C) * (alkaline)
Kinematic viscosity	not relevant
Solubility(ies)	not determined

#### Partition coefficient

n-octanol/water (log KOW)	not relevant (inorganic)
---------------------------	--------------------------

Vapour pressure	not determined
-----------------	----------------

#### Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	no data available
--------------------------	-------------------

#### 9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### Other safety characteristics

Solvent content	0 %
Solid content	100 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

Exhibits an exothermic reaction (with): acids

Dangerous/dangerous reactions with: base metals ( formation of hydrogen)

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

### 10.5 Incompatible materials

There is no additional information.

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Disodium peroxodisulphate	7775-27-1	Oral	1,200 mg/kg
Sodium permanganate	10101-50-5	Oral	500 mg/kg

##### Skin corrosion/irritation

Causes severe skin burns and eye damage.

##### Serious eye damage/eye irritation

Causes serious eye damage.

##### Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
**TM DESANA MAX FP**

Version number: GHS 16.0  
 Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

## Reproductive toxicity

Shall not be classified as a reproductive toxicant.

## Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

## Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

#### Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Potassium nitrate	7757-79-1	LC50	1,378 mg/l	Fish	96 h
Potassium nitrate	7757-79-1	EC50	490 mg/l	Aquatic invertebrates	48 h
Sodium permanganate	10101-50-5	LC50	0.7 mg/l	Fish	48 h
Sodium permanganate	10101-50-5	EC50	0.06 mg/l	Aquatic invertebrates	48 h
Sodium permanganate	10101-50-5	ErC50	0.8 mg/l	Algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Potassium nitrate	7757-79-1	EC50	490 mg/l	Aquatic invertebrates	24 h
Potassium nitrate	7757-79-1	ErC50	>1,700 mg/l	Algae	10 d
Sodium permanganate	10101-50-5	LC50	1.51 mg/l	Fish	24 h
Sodium permanganate	10101-50-5	EC50	0.15 mg/l	Aquatic invertebrates	24 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

### 12.6 Endocrine disrupting properties

Information on this property is not available.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Waste treatment-relevant information

Recycling/reclamation of other inorganic materials.

#### Sewage disposal-relevant information

The application solution can be disposed in the sewage system, taking into account technical and national regulations.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

#### Properties of waste which render it hazardous

HP 4 Irritant - skin irritation and eye damage.  
HP 8 Corrosive.

#### List of wastes

#### Waste catalogue ordinance (Germany)

Assign arising waste to a waste code according to the national list of waste

#### - Product

20 01 15\* Alkalines.

#### - Product residues

15 01 10\* Packaging containing residues of or contaminated by hazardous substances.

#### - Packagings

15 01 02 Plastic packaging.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN UN 3262

IMDG-Code UN 3262

ICAO-TI UN 3262

### 14.2 UN proper shipping name

ADR/RID/ADN CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.

IMDG-Code CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.

ICAO-TI Corrosive solid, basic, inorganic, n.o.s.

Technical name sodium hydroxide, Sodium permanganate

(hazardous ingredients)

### 14.3 Transport hazard class(es)

ADR/RID/ADN 8

IMDG-Code 8

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

<b>14.4</b>	<b>ICAO-TI</b>	8
	<b>Packing group</b>	
	<b>ADR/RID/ADN</b>	II
	<b>IMDG-Code</b>	II
<b>14.5</b>	<b>ICAO-TI</b>	II
	<b>Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6</b>	<b>Special precautions for user</b>	
	Provisions for dangerous goods (ADR) should be complied within the premises.	
<b>14.7</b>	<b>Maritime transport in bulk according to IMO instruments</b>	
	The cargo is not intended to be carried in bulk.	

### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Classification code	C6
Danger label(s)	8



Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 kg
Transport category (TC)	2
Tunnel restriction code (TRC)	E
Hazard identification No	80
Emergency Action Code	2X

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	-
Danger label(s)	8



Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 kg
EmS	F-A, S-B
Stowage category	B
Segregation group	18 - Alkalis

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
**TM DESANA MAX FP**

Version number: GHS 16.0  
 Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

## International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 8



Special provisions (SP) A3  
 Excepted quantities (EQ) E2  
 Limited quantities (LQ) 5 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### Deco-Paint Directive

VOC content 0.046 %

##### Industrial Emissions Directive (IED)

VOC content 0 %

##### Regulation 648/2004/EC on detergents

Labelling of contents	
Constituents	Weight % content (or range)
Phosphates	30 % and more

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

Abbr.	Descriptions of used abbreviations
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
Met. Corr.	Substance or mixture corrosive to metals
M-Factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
Ox. Sol.	Oxidising solid
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Resp. Sens.	Respiratory sensitisation
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## TM DESANA MAX FP

Version number: GHS 16.0  
Replaces version of: 2020-08-04 (GHS 15)

Revision: 2021-10-28

Abbr.	Descriptions of used abbreviations
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TRGS	Technische Regeln für GefahrStoffe (technical rules for hazardous substances, Germany)
TWA	Time-weighted average
VOC	Volatile Organic Compounds
VPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.  
health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.